



## **Technical Details**



## **Standard Equipment**

- rigid frame (Retro or Taurus) made of aluminum, SW and BH grows (opt. also SD), tight wheel base
- · 2 differently strong V-formed abductions
- seat unit mechanically tiltable from -5° to 35°
- back angle from 78°-126° adjustable and the back folds down to the front
- firm seat plate made of aluminium (SitzFix)
- standard, light weight or profile wheels (built-in hand rims) with quick release axle, pneumatic-tired or flat free
- stabilising rod
- active side guards (combination of aluminum and synthetic) with built-in cable brake
- · casters with alu-fork in different versions
- · many different varnish varieties





The back angle is adjusted in small raster steps.
The metabolism, cardio-vascular system and breathing are stimulated by the change of position

- different positioning aids (head rests, truss pads, belts, anatomically formed seat and back units, abduction
- · also suitable for mounting a seat shell

wedge)

- different one-hand aids (double hand rims, one-hand steering, one-hand brake)
- different back depressions, also with submersible back extention
- extention of the seat plate 4 cm (SitzFix)

- foot plate continuous or split, swings to the side or swings up
- height and angle adjustable push handles or bail
- steer and push aid for outside (Outdoor Front End)
- over 250 different spoke guard designs
- seat and back cushion in many different colours
- · special tires and handrim covers.

e by SOR Rollstuthlershink (DMH 4- RO. K/G Benzstraße 3-5; 6879-4 Oberhausen-Reinflausen, Germr Fin. 449 725-42-927-0 Eusen in infegeorgelist Fax 449 7254-8279-10 Web was orggelists Was ere earlies according to the Quality-Management System in Increase and released or the Quality-Management System in